



 Proudly  
made in Italy



# Alyssa B18 & Alyssa B23

B-class 18 and 23-liter autoclaves



## Cycle Recording via Wi-Fi

Automatically record performed cycles to your computer via Wi-Fi and Ethernet as printable PDF files.



## Sterile Instrument Labels

To trace each kit's sterility status and traceability compliance, the SterilPrint printer produces key sterilization details.



## Remote Monitoring

Monitor the cycle's status from a distance via the Remote LED Indicator.



## Cycle Choice Assistant

Reduce water and electricity consumption, save time, and preserve your high-value instruments by selecting the optimal cycle for your load with Cycle Choice Assistant.



## Built-In Reverse Osmosis

Include ROSI® to effortlessly connect your unit to tap water. This configuration offers an impressive average of 1,300 cycles of operation before maintenance is required.



## Standard Water Pump

Thanks to the built-in frontal water pump, you can keep the tank on the ground. Simply press a button, and the autoclave will fill itself up.

Sterilization Cycles	Alyssa B18	Alyssa B23
Universal-B (134°C, steriliz. time: 5 min)	27 min	37 min
Quick-S (134°C, steriliz. time: 5 min)	19 min	29 min
Gentle-B (121°C, steriliz. time: 18 min)	40 min	50 min
Quick-B (134°C, steriliz. time: 5 min)	20 min	30 min
Universal-S (134°C, steriliz. time: 5 min)	32 min	42 min
Gentle-S (121°C, steriliz. time: 18 min)	43 min	53 min
Prion-B (134°C, steriliz. time: 20 min)	39 min	49 min
Test	Helix / Bowie-Dick / Vacuum	Helix / Bowie-Dick / Vacuum

Note: Values include pre-heating and drying; times vary with load and power supply.

Technical Specifications	Alyssa B18	Alyssa B23
Autoclave Class	B	B
Chamber Volume	18 L	23 L
Chamber Dimensions (Ø x d)	236 x 380 mm	236 x 530 mm
Chamber Max. Fitting Cuboid Dimensions (w x d x h)	166 x 345 x 166 mm	166 x 529 x 166 mm
Max. Load Quantity	2.5 kg wrap. instr. 4 kg unwrap. instr. 1 kg textiles	3.5 kg wrap. instr. 4.5 kg unwrap. instr. 1.5 kg textiles
Device Dimensions (w x d x h)	520 x 670 x 400 mm	520 x 670 x 400 mm
Weight	45 kg	47 kg
Power Supply	220 - 240 V 50 - 60 Hz	220 - 240 V 50 - 60 Hz
Power Consumption	2,400 W	2,400 W



Label Printer



Ultrasonic Baths



Heat Sealer